

When filling sacks with dusty materials, it is essential to minimise dust emissions to protect operators and the environment. Some manufacturing systems only process small amounts of constantly changing products, and do not warrant the use of automated plants. For these applications we offer three different systems of manually operated sack tip stations:

EMDE sack discharger type SE
Enclosed EMDE sack emptying booth type SK
EMDE sack chute type ST

The wide variety of products to be discharged and many diverse applications led to the development of these three different emptying systems. They can be used with any configuration of commercially available conveying and dosing facilities.

Enclosed EMDE sack emptying booth

Fully enclosed, dust-tight design
 Capacity: up to 20 sacks per hour
 Operation from outside via a glovebox system
 Sack knife: secured in dust collecting hood with chain

EMDE sack chute:

Compact design
 Easy to clean and disinfect
 Very easy to operate
 High emptying capacity up to 120 sacks/h possible

... All round – simply clean EMDE Sack Emptying Systems

EMDE sack discharger:

Dust emissions eliminated
 Ergonomically designed operation
 Emptying flap can also be used as a safety door with lock
 Simple operation
 Emptying capacity: up to 60 sacks per hour



35

EMDE sack discharger for use with additives



36

Mobile EMDE sack discharger with lump crusher for pharmaceutical products



37

EMDE sack chute for powdered milk



38

Inside view of the EMDE sack emptying booth



39