Fristam FPM / FSM









Centrifugal pump / shear pump FPM / FSM

Specifically suited for transferring toxic, dangerous or WHC goods. These magnetically coupled pumps are designed for applications with special safety requirements. The open impeller is connected to the driving unit via a magnetic coupling that is contact-free. The product space is hermetically sealed from the environment by a separating can.

SPECIFICATIONS*

Design

Solid stainless steel structure in monobloc design with an open impeller connected to the drive unit via a magnetic coupling.

Construction

Material



The pump power is transmitted from the drive shaft contact-free via the magnetic coupling. This ensures that the pump speed always corresponds to the drive speed. Thanks to the special bearings of the magnetic coupling's internal rotor, only the drive speed is transmitted to the drive shaft, avoiding any undesirable forces.

The Fristam FSM is available as a shear pump featuring a combination of rotor and stator that produces homogenised multiphase products of supreme quality.

Stainless steel 1.4404 (316L),

alternative materials upon request

Separating can Hastelloy (standard), PEEK or ceramics

(upon request)

Magnetic coupling as hermetic sealing -Sealing

no mechanical seal

Mounting To suit requirements

350°C Max. temperature



BENEFITS AT A GLANCE

- No mechanical seal; no need for a locking or supply system
- Hermetic sealing between product and atmosphere
- For transferring toxic, dangerous and WHC goods
- Smooth transfer of liquids with solids content of up to 5 wt%



^{*} Please note that the technical information provided above is subject to further development of the product range.